



备注:

- 材质:
  - 1-1 塑胶: LCP(黑色)
  - 1-2 端子: 黄铜C2680
  - 1-3 铁壳: SPCC
- 电镀:
  - 端子接触区域: 镀金G/F (0.5).
  - 端子锡脚: 镀亮锡80u"min.
  - 端子整个表面: 镀镍30u"min.
  - 铁壳: 镀镍30u"min
- 电气性能:
  - 3-1 额定电流: 1.5A
  - 3-2 耐电压: 500V 交流电
  - 3-3 接触电阻: 50 毫欧 最大
  - 3-4 绝缘阻抗: 1000 兆欧最小
- 机械性能:
  - 4-1 插入力: 3.5kgf MAX
  - 4-2 拨出力: 0.7kgf MIN
- 环境:
  - 温度范围: -55° C TO +85° C
- 零件必须符合ROHS标准.
- 产品必须过盐雾12H

REV.	ECN. NO.	DRAWN	DATE	EC.content
A	NEW	LLDONG	12/15/2015	-



⊗: QUALITY CONTROL ITEM		GENERAL TOLERANCE		PART NO.: YK-UBD18-3KM1-041		
APPROVED		.X± 0.38	X.*± 2'	TITLE:A/F 短体10.0 DIP外壳		
CHECKED		.XX± 0.25	.X.*± 1'	两脚有卷边H=6.8		
DRAWN		.XXX± 0.13		UNIT: mm	SCALE: 1:1	SHEET: 1/1
						REV.: A

說明: △ :備註 ◇ :版本變更 ① :尺寸序號 ■ :重點尺寸 ▼ :CPK尺寸 DOCUMENT NO. : ZER0013/A.3

1 2 3

SIZE: A4