



NOTE:

- MATERIAL:
 - INSULATOR:LCP UL 94V-0
 - CONTACT:BRONZE (T=0.20mm)
 - SHELL:BRASS (T=0.30mm)
- ELECTRICAL CHARACTERISTICS;
 - CONTACT RESISTANCE:30mΩ MAXIMUM
 - CONTACT CURRENT RATING:1.5A
 - DIELECTRIC WITHSTANDING VOLTAGE:500 V R. M. S.
 - INSULATION RESISTANCE 1000 MEGOHMS MIN
 - OPERATING TEMPERATURE:-40° C ~ 85° C
- MECHANICAL CHARACTERISTICS:
 - MATING FORCE:3.57kg MAX
 - UNMATED FORCE:1.02kg MIN
 - DURABILITY:MANDATORY:1,500 CYCLES
- PLATING
 - TERMINAL:
 - 50u" MIN NICKEL ALL OVER
 - 80u"MIN Tin ON SOLDER AREA
 - (1~30)u"Au ON CONTACT AREA
 - SHELL:100u"MIN. NICEL ALL OVER

Pin NUMBER	SIGNAL NAME
1	VBUS
2	D-
3	D+
4	GND
5	StdA_SSRX-
6	StdA_SSRX+
7	GND_DRAIN
8	StdA_SSTX-
9	StdA_SSTX+
Shell	Shield

REV.	ECN. NO.	DRAWN	DATE	EC.content
A	NEW	LLDONG	05/05/2016	-
A.1	EN1609002	LLDONG	09/12/2016	包装方式由吸塑盒改为卷盘



(X) QUALITY CONTROL ITEM APPROVED CHECKED DRAWN		GENERAL TOLERANCE .X± 0.38 X.° ± 2' .XX± 0.25 .X° ± 1' .XXX± 0.13	PART NO.: YK-WU3F095M12T00R TITLE:USB 3.0 AF SMT 沉板 沉板 沉板 有卷边		
UNIT: mm		SCALE: 1:1	SHEET: 1/1	REV.: A.1	

說明: △ :備註 ◇ :版本變更 ⊙ :尺寸序號 ■ :重點尺寸 ▼ :CPK尺寸 DOCUMENT NO. : ZER0013/A.3

A

F

E

D

C

B

F

E

D

C

B

SIZE: A4