



- NOTES:
- 材质: C7025 TM04, 厚度: 0.15mm;
 - 不可有任何压伤, 毛边最大0.02mm, 折弯处不可有电镀无法覆盖之折弯痕, 折弯处涨料后宽度尺寸须在标注尺寸内, 未标注之R角为R0.10mm最大, 折弯外R为R0.24mm, 端子电镀须进行油性封孔, 焊接区电镀须通过WETTING BALANCE测试;
 - 电镀前和电镀后零件均须符合RoHS相关规定;
 - 电镀规格:
 - 5-1 基层电镀40-60u"镍底
 - 5-2 A区域: 接触区, 镀金(见料号可选)
 - 5-3 B区域: 焊接区, 雾锡60-120u"
 - 此部品, 禁止使用含有《环境管理物质控制标准》所限制的物质作为材料;
 - "■" SHOWS QIP INSPECTION POINT.
 - "⊗" SHOWS FAI MEASUREMENT POINT.
 - " " SHOWS CPK MEASUREMENT POINT.

RoHS2	15μ"	3341-03038-031
	G/F(1u")	3341-03018-031
	NO PLATING	3341-00008-031
GP TYPE	PLATING	PART NUMBER

REV.	ECN. NO.	DRAWN	DATE	EC.content
A	NEW	WuQiangYuan	11/12/15	-



⊗: QUALITY CONTROL ITEM	GENERAL TOLERANCE .X±0.10 X:±3" .XX±0.05 X:±3" .XXX±0.03	PART NO.: 3341-XXXX8-031
APPROVED		TITLE: WMF 二排焊線式 10PIN TERMINAL
CHECKED		
DRAWN	吳強遠 15.11.12	UNIT: mm
		SCALE: 1:1
		SHEET: 1/1
		REV.: A