



- W U M-D 3 2 5-5 2 1 0
- D: 母頭
 - 3: Housing LCP BLACK
 - 2: DIP BRASS
 - 5: 5PIN
 - 1: 無定位柱
 - 2: 卷帶包裝
 - 5: 15U' GOLD

Note:
 1. Material:
 1.1 Housing: High temperature thermoplastic with g.f, UL94v-0
 1.2 Contact: copper alloy, t=0.20mm
 1.3 Shell: copper, t=0.25mm
 2. Specification:
 2.1 Current rating: 1,5PIN 1.8A Max/2,3,4PIN 1A Max.
 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
 2.3 Contact resistance: 30 mΩ Max.
 2.4 Insulation resistance: 100 MΩ Min.
 2.5 Total mating force: 3.57 Kgf Max.
 2.6 Total unmating force: 1.0 Kgf Min.
 2.7 Temperature range: -30°C~80°C

REV.	ECN. NO.	DRAWN	DATE	EC.content
A	NEW	Cary	05/18/2015	-



⊗: QUALITY CONTROL ITEM	GENERAL TOLERANCE .X± 0.15 X: ± 2' .XX± 0.10 .X: ± 1' .XXX± 0.05	PART NO.: WUM-D325-5210		
APPROVED		TITLE: Micro usb 5P B Type dip 無定位柱		
CHECKED		UNIT: mm	SCALE: 1:1	SHEET: 1/1
DRAWN				REV.: A