



Recommended P.C.B Layout (±0.05) TOP

- 备注:
- 材质:
 - 1-1 塑胶: PBT(白色)
 - 1-2 端子: 黄铜C2680
 - 1-3 铁壳: SPCC
 - 电镀:
 - 端子接触区域: 镀金G/F (0.5).
 - 端子锡脚: 镀亮锡80u"min.
 - 端子整个表面: 镀镍30u"min.
 - 铁壳: 镀镍30u"min
 - 电气性能:
 - 3-1 额定电流: 1.5A
 - 3-2 耐电压: 500V 交流电
 - 3-3 接触电阻: 50 毫欧 最大
 - 3-4 绝缘阻抗: 1000 兆欧最小
 - 机械性能:
 - 4-1 插入力: 3.5kgf MAX
 - 4-2 拨出力: 0.7kgf MIN
 - 环境:
 - 温度范围: -55° C TO +85° C
 - 零件必须符合ROHS标准.
 - 产品必须过盐雾12H

REV.	ECN. NO.	DRAWN	DATE	EC.content
A	NEW	LLDONG	09/14/2015	
B	EN1601001	LLDONG	12/29/2015	变更供应商, 脚长尺寸变短
B1	EN1609010	LLDONG	09/27/2016	依实物修改端子焊锡端宽度尺寸



⊗: QUALITY CONTROL ITEM		GENERAL TOLERANCE		PART NO.: YK-UBD12-3WM1-041			
APPROVED		.X± 0.13	X.'± 2'	TITLE: USB A TYPE180° 弯脚 插板式 (短: 13.70) 白色			
CHECKED		.XX± 0.08	.X'± 1'				
DRAWN		.XXX± 0.05		UNIT: mm	SCALE: 1:1	SHEET: 1/2	REV.: B1