


**MATERIALS**

- 1. HOUSING : L.C.P (UL 94V-0), BLACK.
- 2. TERMINAL : BRASS, (t=0.20mm)  
GOLD PLATED ON CONTACT AREA,  
TIN PLATED ON SOLDER TAIL,  
UNDER NICKEL PLATED OVER ALL.
- 3. SHELL : STAINLESS STEEL,(t=0.40mm),NICKEL PLATING.

**SPECIFICATION**

- 1. CURRENT RATING : 0.5 A MAX.
- 2. DIELECTRIC WITHSTANDING VOLTAGE :  
500V AC R.M.S. FOR ONE MINUTE.
- 3. CONTACT RESISTANCE : 30mΩ MAX.
- 4. INSULATION RESISTANCE :  
100 MΩ MIN. AT 500V DC.
- 5. OPERATING TEMPERATURE : -25°C TO +85°C.
- 6. MATING FORCE : 4.5kgf MAX.
- 7. UNMATING FORCE : 1.0~4.0kgf
- 8. DURABILITY : 10000 CYCLES.



REV.	ECN. NO.	DRAWN	DATE	EC.content
A.0	NEW	Candy	08/01/2019	



⊗: QUALITY CONTROL ITEM	GENERAL TOLERANCE .X± 0.38 X.'± 2' .XX± 0.25 .X'± 1' .XXX± 0.13	PART NO.: WHD-3001
APPROVED		TITLE: 365FA19-XN601T-H
CHECKED		
DRAWN	UNIT: mm	SCALE: 2:1 SHEET: 1/1 REV.: A.0

SIZE: A4